



Representative Product Image

## Description

The TLP-ED low profile electric defrost unit cooler is designed for -30°F to 34°F room temperatures. The TLP-ED includes corrosion resistant stainless steel heater elements face mounted on the entering air side of the coil allowing for easy service and accessibility. A stainless steel heater element is supplied below the coil for improved condensate removal. The unit includes a factory mounted combination fan delay/defrost termination thermostat control (fixed setting). Units can be field modified for 3 phase heater wiring.



## Product Details

<b>Part No.:</b>	TLP105DED
<b>BTUH -20°F at 10°F T.D.:</b>	10500
<b>Voltage:</b>	208-230/1/60
<b>CFM:</b>	2400
<b>Number of Motors:</b>	3
<b>Length (In.):</b>	68 7/8
<b>Width (In.):</b>	13 3/4
<b>Height (In.):</b>	16 3/4
<b>Connection Suction (In.):</b>	7/8
<b>Connection Size Inlet (In.):</b>	1/2
<b>Connection Type:</b>	ODS
<b>Shipping Weight (Lbs.):</b>	118
<b>BTUH 20°F at 10°F T.D.:</b>	12390
<b>Closeout:</b>	yes
<b>Engineered Items:</b>	Yes
<b>Heater Amps:</b>	15.4
<b>Heater MCA:</b>	19.3
<b>Heater Watts:</b>	3550
<b>LTL Only:</b>	Yes
<b>Vendor:</b>	Trenton Refrigeration Products
<b>Web Description:</b>	Unit cooler, walk-in, electric defrost, low profile, 12390 BTUH 20°F ET, 208-230/1/60, 16 3/4" H x 68 7/8" W x 13 3/4" D